

C2

have the dimensions (X-direction) of from about 40 cm to about 80 cm, and (Y-direction) of from about 40 cm to about 80 cm. Two or more smaller carrier sheets can be used when a larger surface area is desired (or needed) as is discussed above.

BEST AVAILABLE COPY

Please replace the paragraph at page 26, lines 27-32 with the following paragraph:

C3

Step 2. Following the pre-spotting step, the fabric article is placed into a conventional clothes dryer together with the sheets (which are removed from the storage pouch and unfolded) releasably containing the liquid cleaning/refreshment composition of Example II. The dryer is operated in standard fashion for 10-60 minutes at a high heat setting (an air temperature range of about 140-170°F; 60-76.7°C). After the tumbling action of the dryer ceases, the cleaned and refreshed fabric article is removed from the dryer. The used carrier sheets are discarded.

Please replace the paragraph at page 28, lines 18-23 with the following paragraph:

C4

With respect to the wrinkle-removing function of the in-dryer step of the process and the compositions herein, it will be appreciated that wrinkling can be affected by the type of fabric, the fabric weave, fabric finishes, and the like. For fabrics which tend to wrinkle, it is preferred not to overload the dryer. Thus, for a dryer with, for example, an operational capacity of up to about 3.5 to 7.0 cubic feet (99,110 to 198,200 cubic centimeters), it may be best to process up to only about 35% to about 40% of the dryer capacity, to further minimize wrinkling of the fabric articles.

#### IN THE CLAIMS

Please amend the following Claim:

C5

11. (Amended) A bagless kit for dry cleaning fabrics comprising one or more carrier sheets that releasably comprise an amount of a liquid cleaning/refreshment composition such that when fabrics are exposed to said liquid cleaning/refreshment composition within a heating vessel, in the absence of a bag, the fabrics are cleaned.

C6

13. (Amended) A method for cleaning fabrics in need of cleaning comprising:

- a) placing the fabrics in a heating vessel;
- b) placing a carrier sheet that releasably comprises an amount of a liquid cleaning/refreshment composition, such that when the fabrics are exposed to said liquid cleaning/refreshment composition the fabrics are cleaned,